

**OLIFF & BERRIDGE, PLC**

ATTORNEYS AT LAW

April 15, 2004

**RECEIVED  
CENTRAL FAX CENTER****APR 15 2004  
OFFICIAL**277 SOUTH WASHINGTON STREET  
ALEXANDRIA, VIRGINIA 22314TELEPHONE: (703) 836-6400  
FACSIMILE: (703) 836-2787E-MAIL: O&B@OLIFF.COM  
WWW.OLIFF.COM**FACSIMILE TRANSMISSION COVER SHEET**

To: 703-872-9306  
571-273-2094  
Examiner Thanh Tam T Le  
U.S. Patent and Trademark Office  
Group Art Unit 2839

From: Jude CooneyYour Ref.: 10/006,204Our Ref.: 111412Number of Pages Sent (Including cover sheet): 5Prepared By: JLC**Comments:**

Enclosed as the Appendix is claim 2 amended in accordance with our discussion on April 13. Please prepare an Examiner's Amendment incorporating the changes to claim 1 as shown in the Appendix. Moreover, attached is a copy of the IDS and Form PTO-1449 filed March 22. Please consider the IDS and references cited therein when you prepare the Examiner's Amendment. If you have any further questions or comments please contact me.

Sent by: \_\_\_\_\_

This facsimile is intended only for the use of the individual or entity named above and may contain privileged or confidential information. If you are not the intended recipient, or the employee or agent responsible to deliver it to the intended recipient, you are notified that any review, dissemination, distribution or copying of this facsimile is prohibited. If you have received this facsimile in error, please immediately notify us by facsimile or telephone, and return the facsimile to us by mail at the above address.

APPENDIX

2. (Currently Amended) A connector assembly comprising:  
for a flat wire member including conductors and an end portion split into a plurality of  
split pieces, comprising:

a first connector including terminals accommodated therein; and  
a plurality of second connectors for respectively holding split pieces of the flat wire  
member in a state that portions of the conductors are exposed;

wherein the first connector includes a plurality of coupling portions to be respectively  
coupled with the plurality of second connectors, and the terminals are so accommodated in  
the first connector as to be brought into contact with the exposed portions of conductors of  
the flat wire member when the second connectors are respectively coupled with the coupling  
portions, wherein the coupling portions of the first connector are arranged on one side of the  
first connector side by side in widthwise direction of the flat wire member;

wherein the first connector further includes an insertion portion which is provided at a  
side opposite from the side where the coupling portions are arranged and which receives an  
end portion of a second flat wire member, with each terminal being brought into contact with  
a corresponding conductor of the second flat wire member to connect the conductor of the  
second flat wire member with a corresponding conductor of the flat wire member held by the  
second connectors.